

Polaroid Everest E 2.0

Hybrid UV LED

Head Option

Ricoh G6 5 PL

Printing Speed

Heads	4 Pass	6 Pass	8 Pass
3	323 ft ² /h	193 ft ² /h	150 ft ² /h
6	516 ft ² /h	365 ft ² /h	301 ft ² /h
9	839 ft ² /h	570 ft ² /h	452 ft ² /h



Curing System	UV LED Curable Ink
Ricoh G6	From 2 up to 9 print heads
Color Option	C M Y K + W + Varnish (Optional)
Printing Mode	Unidirectional / Bi-directional
Media Thickness	2 inches
Rip	Photo Print
Resolution	1200 DPI
Ink Type	UV LED
Media	Glass, Acrylic, Wood, PVC, Metal Panels, Ceramic Tiles, KT board WPC, MDF, Ceiling Film, Vinyl, Advertising Banner, PET, Wall paper and so on
Power Supply	50/60HZ 220V (10%)> 30A
Operation Conditions	Temperature 68° f - 74° f Relative Humidity 40% to 60%
Printer Dimensions	14.40ft x 4.97ft x 4.92ft / 4392x1515x1500mm
Packaging Dimensions	15.09ft x 7.44ft x 6.33ft / 4600x2270x1930mm
Recommended Placement Area	18.04ft x 16.40ft / 5500x5000mm

